



RAPID ROLL **Doors**



HIGH SPEED DOORS MODELS



Doors for outdoor use

These doors are resistant to strong winds loads thanks to its reinforced design. Usually there are speed doors with stackable lifting system, but there may be some exceptions.



Instant Pass®




Instant Pass® PREMIUM



Instant Pass® BASIC



Instant Pass® ECO



Grand Pass® (Big dimensions)

Doors for indoor use

These doors are resistant to strong winds loads thanks to its reinforced design. Usually there are speed doors with stackable lifting system, but there may be some exceptions.



Instant Roll®



Instant Roll® ECO



Instant Roll® BASIC



Easy Roll®




Mirflex® AUTO TRACKING



Mirflex® ECO AUTO TRACKING



Mirflex® ZIP AUTO TRACKING



Mono Pass® NOVOSPRINT (horizontal)



Doble Pass® NOVOSPRINT (horizontal)



Doble Pass® NOVOSPRINT HIGYENIC (horizontal)

Doors for special use

These doors are designed for a specific sector, considering each technical needs. The opening can be rolling or stackable.




Instant Pass® ISO (for cold rooms)




Hermetic Roll® for clean rooms (at pharmaceutical industry)



Instant Protect® (robots and machines)



Easy Roll® INSECT (mosquito net)



Instant Roll C3® (for cold & refrigerated rooms)

Model INSTANT ROLL®



Instant Roll®



Instant Roll® in a logistics centre.



Instant Roll® with front motor.

The outer frame is a self-supporting frame made of galvanised and painted steel plate, made up of two posts, which act as guides and supporting base (the edges that come into contact with the fabric are protected by industrial brushes which minimize friction and increase the seal), and an upper beam in the form of an accessible drawer.

The aluminum roller shaft is inside the platform, mounted on supports with bearings. The curtain rolls onto the shaft. The structure is self-supporting and is secured with simple reinforcement anchorage and thus does not require major fastening systems on site.

Canvas specifications

The canvas has a series of transversal reinforcements, which provide the resistance required for the air pressure currents it will endure.

The lower skirting is a PVC bag, enabling perfect adjustment on uneven floors. The

bag is painted in yellow and black stripes, for greater identification of the transit area.

Applications:

- Agro food industry.
- Supermarkets.
- Shopping centres.
- Laboratories.
- Industries.

Recommendations

It is designed to fit in almost any space. Special situations that do not enable standard configurations to be adapted may be studied by the Angel Mir projects department.

Options

- Emergency opening system by means of UPS or mechanical system.
- AISI 304L and 316L stainless steel structure.
- ATEX certified doors for explosive environments. Powder, paint or gas.
- See-through canvas.
- Double isolation canvas.

Access security

Option 1: Wireless contact band on the main edge and infra-red barrier at 500 mm from the floor.

Option 2: Infra-red curtain up to 2.5 m height. This system has a series of photocells fitted one on top of another that create the infra-red barrier on the entire height of the door and up to 2.5 m high, which detects any object, including small objects, preventing lowering the door or raising it again if it has already begun to lower. Avoids physical contact with the door.

Performance of the air

Wind resistance as per 12424:
Class 1 up to 4,000 x 4,000 mm.
Class 0 up to 5,000 x 5,000 mm.

Maximum dimensions

5,000 x 5,000 mm.



HIGH SPEED DOORS

INSTANT
PASS

GRAND
PASS

**INSTANT
ROLL**

HERMETIC
ROLL

INSTANT
PROTECT

EASY ROLL

MIRFLEX

GENERAL
SPECIFICATIONS &
APPLICATIONS

OPENING
SIDE
DOORS



Instant Roll® in food industry.



Instant Roll® two-colour canvas in the pharmaceutical industry.




Instant Roll® with see-through canvas in cars reception.



Instant Roll® in food industry.

Installation measurements Instant Roll® (mm.)



The figures provided here are intended for guidance only. Please ask our sales department to confirm any information.

Model **INSTANT ROLL® ECO**



Instant Roll® ECO is the lightweight version of the Instant-Roll door. It has adequate provisions for medium size openings with moderate air pressure for indoor use.

Structure

The curtain is situated between two mountings in a U shape, which act as a guide and support base for the entire set. It is reinforced, on the inside, with profiles that provide the resistance required to resist the forces it will be subject to and to withstand the weight and forces of the upper shaft with the curtain and the motor. A rounded aluminium profile is mounted on the outside edge which, in addition to reinforcing the base, reduces friction on the canvas.

There is an industrial brush on the inside edge, which minimises air entry and smoothes friction on the canvas. The supports are situated on the head, which support the aluminium shaft, mounted on ball bearings, on to which the curtain rolls and the motor is fastened. They are made from galvanised steel and pre-lacquered in white and the supports and other accessories are made from galvanised steel in different thicknesses depending on the application requirements. The bases are fastened to the floor and the head to a light structure that prevents swaying. In order to ensure greater resistance to frontal forces, one or two middle fastenings are required depending on the height. The shaft can optionally be covered with a sheet cover pre-lacquered in the same colour as the mountings.

Curtain specifications

The canvas has a series of lengthwise reinforcements, which provide rigidity and the resistance required for the air pressure currents it will endure. A concave/convex profile made of "composite" materials is sheathed in the curtain.

This profile has extraordinary resistance to breaking (even with violent impacts from moving vehicles) and can withstand significant flexing without causing permanent deformations. The lower skirting is a PVC bag, enabling perfect adjustment even on uneven surfaces. The bag is painted in yellow and black stripes, for greater identification of the transit area.

Motor and control panel

Compact self-locking reducer motor for intensive use with integrated position mechanical switches. Internal safety catch.

Electro-brake for exact positioning and locking the canvas. Manual release of the electro-brake with handles. Manual opening system with a crank or chain.

Control panel: Single phase 220 V power supply and control panel with programmable automaton and with a frequency converter for regulating speeds.

Access security

Infra-red curtain up to 2.5 m height. This system has a series of photocells fitted one on top of another that create the infra-red barrier on the entire height of the door and up to 2.5 m high, which detects any object,

including small objects, preventing lowering the door or raising it again if it has already begun to lower. Avoids physical contact with the door.

Options

- Emergency opening system via UPS with single phase panel.
- AISI 304L and 316L stainless steel structure.
- Double canvas
- See-through canvas
- Sealing joints

Performance of the air

Wind resistance as per 12424: Class 0.

Dimensions

Maximum: 4,500 x 4,500 mm.



Detail of infra-red barrier.

HIGH SPEED DOORS

INSTANT
PASS

GRAND
PASS

**INSTANT
ROLL**

HERMETIC
ROLL

INSTANT
PROTECT

EASY ROLL

MIRFLEX

GENERAL
SPECIFICATIONS &
APPLICATIONS

OPENING
SIDE
DOORS



Instant Roll® ECO in repair workshop.



Sealing joints and double canvas option.




Instant Roll® ECO in freezing logistic center.




Instant Roll® ECO STAINLESS version.


Installation measurements Instant Roll® ECO (mm.)




Standard




With motor cover (optional)




Standard



With motor cover (optional)



With front and rear covers



(A) For clear width over 3.000 A=100
(A) For clear width over 3.000 A=150

The figures provided here are intended for guidance only. Please ask our sales department to confirm any information.

Model INSTANT ROLL® BASIC



Instant Roll® BASIC STAINLESS with simple canvas.


The speed rolling door Instant Roll BASIC are suitable for medium-sized voids located indoors and having an intense flow, as in production and storage areas. They have been designed to occupy a minimal space and capable to withstand light air pressures-depressions.

Features of the canvas

The canvas incorporates a number of longitudinal reinforcements providing stiffness through a concave-convex tubular profile, made with "composite" materials, that is inserted into a cladding on the canvas. This profile counts on an extraordinary resistance to breakage (even through violent impacts made by vehicles in movement) and a great flexibility, so it can bend without permanent deformations.

The lower sole is a band, thanks to it a perfect adjustment even in irregular floors is achieved. The mentioned band is screen printed with the safety symbols

Installation measurements Instant Roll® BASIC (mm.)



The figures provided here are intended for guidance only. Please ask our sales department to confirm any information.

- black and yellow diagonal stripes - indicating the danger in areas having vehicles flow.

Structure

The structure is self-supporting thanks to the guide reinforcement profiles made of prelacquered galvanized sheet, and to its upper platform built with the same material.

Motor and control panel

The door Instant Roll Basic carries an irreversible compact geared motor for intensive use. On the other hand, the standard configuration of the operation panel comes equipped with a frequency variator allowing a high speed of lifting and a descent at reduced speed, with soft starts and stops. So, the strong impacts of the starting and stopping of the engine are eliminated, improving therefore its reliability.

Access security

Standard: curtain of photocells placed one above the other creating an infrared curtain across the door width and up 2.5 m. height. This infrared curtain detects any object, including small ones, preventing the door lowering or lifting again if it has already started to go down. Avoids physical contact with the door.

Options

The finish of the canvas may be in various colours similar to RAL, while the structure finish can be in galvanized steel or also in a RAL colour chosen by the customer.

Performance of the air

Wind resistance as per 12424: Class 0.

Dimensions

Maximum: 3,300 x 3,500 mm



Instant Roll® BASIC with double canvas.

Model HERMETIC ROLL® (for clean rooms)

The speed rolling door Hermetic Roll overcomes small size voids, ideal for the pharmaceutical industry. It has been designed to have a low permeability to the air and a good resistance to air pressures, making it perfect to be installed in clean rooms having positive or negative pressure. It prevents dirt accumulation. The top hood is inclined to favour the runoff of the materials placed on top.

Features of the canvas

The canvas is made with PVC fabric of high longitudinal flexibility and transversal rigidity. As longitudinal reinforcements are not needed, the canvas is smooth, without protuberances or edges. Standard colour: white PVC smooth on both sides. There are other colours with rough surface and FDA quality, or antistatic fabric (only grey colour).

Options

Viewing windows manufactured with PVC glass quality 2 mm. thickness.

Performance of the air

Wind resistance as EN 12424: class 1 / Air permeability as EN 12426: class 2. Loss of air A 30 Pa: Positive pressure below 2 m³ / H m² / Negative pressure below 4 m³ / H m².

Dimensions


Maximum: 2,800 x 2,800 mm.

With vision panels max. 2,500 x 2,800 mm.



Detail guide.

Installation measurements Hermetic Roll® (mm.)



The figures provided here are intended for guidance only. Please ask our sales department to confirm any information.

HIGH SPEED DOORS

INSTANT
PASS

GRAND
PASS

INSTANT
ROLL

HERMETIC
ROLL

**INSTANT
PROTECT**

EASY ROLL

MIRFLEX

GENERAL
SPECIFICATIONS &
APPLICATIONS

OPENING
SIDE
DOORS

Model INSTANT PROTECT®

The speed rolling door **Instant Protect®** is suitable for medium sized voids. Is intended to be used as separating of robotic cells or accesses to machines. This door is resistant to moderate air currents and minor impacts. The structure is designed to be integrated into demanding environments, and the engine and the operation panel for a very intensive use. This door model also incorporates safety stroke limits up to category 4.

Features of the canvas

The canvas is manufactured with PVC fabric having high longitudinal flexibility and transversal stiffness. Longitudinal reinforcements are not required but, in case of higher requirements, the canvas can be reinforced. Standard colour: orange PVC with linen rough surface.

Optionally it can be in other colours. Antistatic fabric (only grey colour).

Options




Viewing windows with PVC glass quality of 2 mm thickness. Integrated into the canvas itself. Possibility to have red peepholes for welding areas. It includes photocells barrier system.

Dimensions

Maximum: 3,500 x 3,500 mm.



Installation measurements Instant Protect®(mm.)



(1) Exemption of installation

The figures provided here are intended for guidance only. Please ask our sales department to confirm any information.

Model **EASY ROLL**®

Ángel Mir® Easy Roll® high speed door is designed for interior openings and for separating different environments, with low air pressures and with reduced corridor spans (up to 3 m wide). It is ideal for replacing awkward slatted curtains and PVC side hung doors.

The design of the outer frame has been simplified and consists of a pair of lateral galvanised plate guides, which support the aluminium roller shaft onto which the curtain winds.

The structure is simple and requires a solid anchorage.

Canvas specifications

The central reinforcements are manufactured from an aluminium bar which also serves to support the central window that can be replaced.

The ends of the lower skirting are made of neoprene which slots into the guides. In the event of an impact, the ends bend and come out of the guides, returning to the correct position in the next operation.

Options

- Emergency opening system via UPS or mechanical system.
- Stainless steel version, particularly suited for the food industry.

Installation recommendations

Some examples of use may be:

- Walkways between buildings
- Supermarkets.
- Warehouses.
- Refrigeration chambers.
- Food industry (STAINLESS version).

Access security

Photocells curtain.

Performance of the air

Wind resistance as EN 12424: Class 0

Dimensions

Maximum: 3,300 x 3,300 mm.

The small size of the structure enables it to be adapted to any opening or environment.



Easy Roll® in the meat industry.




Detail of photocells curtain.



Easy Roll® in fruit industry.

Installation measurements **Easy Roll**® (mm.)



- (1) Exemption
(2) To regulate the limit switch

The figures provided here are intended for guidance only. Please ask our sales department to confirm any information.

Model **EASY ROLL**® INSECT

Manually operated door with canvas of perforated fabric used as a barrier against insects. The drive is manual, easy, and fast and doesn't need electricity. Convenient for production facilities and food handling, or places in need to prevent the entry of insects. Economic price.

Dimensions

Maximum: 3,500 x 3,000 mm.

* For range of colours and types of canvas see page 32.



Easy Roll® INSECT with perforated blue canvas.



Easy Roll® INSECT (manual version).

Model **MIRFLEX ZIP**® AUTO TRACKING

A door completely built with galvanized steel profiles or painted.

The guiding of the door is made via a system of racks located on the sides of a PVC canvas. These flexible racks lead, smoothly, the canvas inside some guides of special polyamide of high resistance and sliding, that prevent that the canvas derails due to the strength of air currents. When the rack gets an impact, it leaves the guide and goes back to the rails when dropping.

These doors are recommended for use indoors or outdoors without wind pressures.

Suitable for: warehouses, supermarkets, separations between industrial units, etc.

Optionally, in places where a nicer aesthetic finish is required, a cover for the drum is proposed.

Dimensions

Maximum: 4,500 x 5,000 mm.



Model MIRFLEX® AUTO TRACKING

A rolling door for medium size openings, ideal for separating different environments and passage ways between buildings, warehouses or stores. Designed with different small size profiles, they take up little of the opening's light space and require little space on the side bracelets and on the lintel. They are resistant to moderate air currents and the curtain has a system of flexible reinforcements that come off the guides when they receive a strong impact and roll up again when the door opens.

Structure

Vertical mountings made up of a reinforced guide made from extruded aluminium and with a specific design for this model door, housed in a double rectangle profile made from 1.5 mm stainless steel.

Galvanised and lacquered. Galvanised and lacquered steel sheet base with eyelets for fastening to the floor. Black polyethylene tracking. Support platform for the rolling drum and the motor made from galvanised and lacquered stainless steel. Aluminium rolling drum with galvanised steel shaft on supports with ball bearings.

The bases are fastened to the floor and the head to a light structure that prevents swaying. In order to ensure greater resistance to frontal forces, one or two middle fastenings are required depending on the height.

Canvas specifications

The canvas has a series of lengthwise reinforcements, which provide rigidity and the resistance required for the air pressure currents it will endure. A concave/convex profile made of "composite" materials is sheathed in the curtain.

This profile has extraordinary resistance to breaking (even with violent impacts from moving vehicles) and can withstand significant flexing without causing permanent deformations. The lower skirting is a PVC bag, enabling perfect adjustment even on uneven surfaces. The bag is painted in yellow and black stripes, for greater identification of the transit area.

Auto tracking system

In the event of impact on the curtain, the sheet bends thanks to the flexibility of the reinforcements and can come off the



Mirflex® AUTO TRACKING in food factory.

guides. When it goes up again, the ends of the reinforcements are reinserted into the guides thanks to the auto tracking system on the lower part. The door is then ready for the next manoeuvre. The system reduces the span width by 80 mm.

Motor and control panel

Self-locking reducer motor for intensive use with integrated position mechanical switches.

Electro-brake for exact positioning and locking the canvas. Manual release of the electro-brake with a handle. Manual opening system with a crank.

Control panel: 220 V single phase power supply and 24 V operating voltage.

Control panel with programmable automaton and frequency converter for speed regulation.

Access security

Option 1: Wireless contact band on the main edge and infra-red barrier at 500 mm from the floor.

Option 2: Infra-red curtain up to 2.5 m height. This system has a series of photocells fitted one on top of another that create the infra-red

barrier on the entire height of the door and up to 2.5 m high, which detects any object, including small objects, preventing lowering the door or raising it again if it has already begun to lower. Avoids physical contact with the door.

Options

- Emergency opening system via UPS or mechanical system.
- AISI 304L and 316L stainless steel structure.
- ATEX certified doors for explosive environments. Powder, paint or gas.

Performance of the air

Wind resistance as per 12424: up to Class 0.

Dimensions

Maximum: 3,300 x 3,500 mm.

Please ask if larger sizes are required.

HIGH SPEED DOORS

INSTANT
PASS

GRAND
PASS

INSTANT
ROLL

HERMETIC
ROLL

INSTANT
PROTECT

EASY ROLL

MIRFLEX

GENERAL
SPECIFICATIONS &
APPLICATIONS

OPENING
SIDE
DOORS



Mirflex® AUTO TRACKING.




Mirflex® AUTO TRACKING.




Mirflex® AUTO TRACKING Stainless.



Installation measurements Mirflex® AUTO TRACKING (mm.)



Side motor



Front motor



- (1) Exemption
- (2) For assembling and disassembling the motor

The figures provided here are intended for guidance only. Please ask our sales department to confirm any information.

Model **MIRFLEX ECO®** AUTO TRACKING

This is the lightweight version of Mirflex® AUTO TRACKING, for medium size openings, ideal for separating different environments and passage ways between buildings, warehouses and stores.

Designed with different small size profiles, they take up little of the opening's light space and require little space on the side bracelets and on the lintel.

They are resistant to moderate air currents and the curtain has a system of flexible reinforcements that come off the guides when they receive a strong impact and roll up again when the door opens.

Structure

Vertical mountings made up of a reinforced guide made from extruded aluminium and with a specific design for this model door, housed in a double rectangle profile with central housing for the guide. Can be delivered lacquered in two colours (Pyrenees white and grey RAL 9007) and stainless steel anodised. Stainless steel sheet base with eyelets for fastening to the floor. Black polyethylene tracking.

The aluminium rolling drum is situated between two stainless steel supports with reinforced bearings that support the shaft.

The bases are fastened to the floor and the head to a light support structure. In order to ensure greater resistance to frontal forces, one or two middle fastenings are required depending on the height.

Canvas specifications

The canvas has a series of lengthwise reinforcements, which provide rigidity and the resistance required for the air pressure currents it will endure. A concave/convex profile made of "composite" materials is sheathed in the curtain.

This profile has extraordinary resistance to breaking (even with violent impacts from moving vehicles) and can withstand significant flexing without causing permanent deformations. The lower skirting is a PVC bag, enabling perfect adjustment even on uneven surfaces. The bag is painted in yellow and black stripes, for greater identification of the transit area.



Mirflex ECO® AUTO TRACKING Stainless.

Auto-tracking system

In the event of impact on the curtain, the sheet bends thanks to the flexibility of the reinforcements and can come off the guides.

When it goes up again, the ends of the reinforcements are reinserted into the guides thanks to the auto-tracking system on the lower part. The door is then ready for the next manoeuvre. The system reduces the span width by 80 mm.

Motor and control panel

Compact self-locking reducer motor for intensive use with integrated position mechanical switches. Internal safety catch. Electro-brake for exact positioning and locking the canvas. Manual release of the electro-brake with handles. Manual opening system with a crank or chain. Control panel. 230/400 V three phase power supply. Electronic control panel.

Option: Single phase 220 V power supply and control panel with programmable automaton and with a frequency converter for regulating speeds.

Options

- Emergency opening system via UPS or mechanical system.

Access security

Option 1: Wireless contact band on the main edge and infra-red barrier at 500 mm from the floor.

Option 2: Infra-red curtain up to 2.5 m height.

This system has a series of photocells fitted one on top of another that create the infra-red barrier on the entire height of the door and up to 2.5 m high, which detects any object, including small objects, preventing lowering the door or raising it again if it has already begun to lower. Avoids physical contact with the door.

Performance of the air

Wind resistance as per 12424: up to Class 0.

Dimensions

Maximum: 3,300 x 3,500 mm.

Please ask if larger sizes are required.

HIGH SPEED DOORS

INSTANT
PASS

GRAND
PASS

INSTANT
ROLL

HERMETIC
ROLL

INSTANT
PROTECT

EASY ROLL

MIRFLEX

GENERAL
SPECIFICATIONS &
APPLICATIONS

OPENING
SIDE
DOORS



Mirflex ECO® AUTO TRACKING with printed canvas.



Mirflex ECO® AUTO TRACKING in food industry.



Photocells curtain.




Mirflex ECO® AUTO TRACKING.



Mirflex ECO® AUTO TRACKING with see-through canvas.

Installation measurements Mirflex ECO® AUTO TRACKING (mm.)



(B) Exemption of installation
(C) To assembling and disassembling the motor

- For total height up to 3m manual operation by crank
- For total height over 3m manual operation by chain

The figures provided here are intended for guidance only. Please ask our sales department to confirm any information.

Canvas specifications and options



Reinforcement bars with rubber caps for reducing wear and tear and noise. For stackable models.



Belt guides and locking clamps made from polyamide to avoid wear and tear and noise. For stackable models.



Resistant bars, light and flexible for absorbing impacts. For stackable models.



Black and yellow skirting detail and red safety strip. For stackable models.



High speed door with outside view screen printed with landscapes or photographs.



Double canvas with insulation. Useful for reducing noise and thermal insulation.



Canvas door printed with text.



Canvas door printed with logos.

The base material is a plastic canvas that is highly resistant to wear and tear and discolouring. A tinted PVC compound is applied to a polyester fabric, producing a canvas that is extremely resistant to breaking and tearing.

The sheaths that support the reinforcements suitable for each type of door and which provide the rigidity and resistance required to support the air currents the sheet will be subject to are welded transversally to the inside part.

Transparent, PVC, 1 mm thickness viewing windows can optionally be installed. This material is resistant to solar radiation, thanks to an integrated UV filter. The weldings that join the canvas are also made with adapted moulds and by high frequency. **These specifications are common to the different high speed door models.**

Canvas specifications

1100 Dtex.


900 g/m².

420/380 daN/5 cm DIN 53354.


70/55 daN 7% ISO 4674.

Both sides.

Glass quality transparent PVC.



High speed door with perforated canvas (outside view).



High speed door with perforated canvas (inside view). To control the entry of people, animals, etc.



A combination of colours on one door.

HIGH SPEED DOORS

INSTANT
PASS

GRAND
PASS

INSTANT
ROLL

HERMETIC
ROLL

INSTANT
PROTECT

EASY ROLL

MIRFLEX

GENERAL
SPECIFICATIONS &
APPLICATIONS

OPENING
SIDE
DOORS

Opening systems



1. Photocell or barrier



2. Handle




3. Radar



4. Remote control



5. Magnetic detector



6. Push button

Canvas models and colours (colours RAL approximate)

STANDARD CANVAS FOR SPEED DOOR

Polyester fabric 1100 dtex coated with PVC and lacquered on both sides.

Roll-up doors (950 gr.)

M2

RAL 1003		Signal yellow
RAL 3002		Carmin red
RAL 5005		Signal blue
RAL 6026		Opal green
RAL 7016		Anthracite grey
RAL 7040		Window grey
RAL 9003		Signal white

M3

RAL 1014		Ivory
RAL 2002		Vermilion
RAL 2004		Pure orange
RAL 8016		Mahogany brown
RAL 9005		Jet black
RAL 9006		Grey aluminium

Fold up doors. FLEXTEx canvas 1000-FR (extremely flexible)

M2

RAL 1003		Signal yellow
RAL 3002		Carmin red
RAL 5005		Signal blue
RAL 7040		Window grey
RAL 9003		Signal white


SPECIAL CANVAS FOR HERMETIC ROLL AND INSTANT PROTECT DOORS

Polyester fabric of double layer with PVC and lacquered on both sides. With rotation direction and lateral stiffness. Approved by the FDA to be in contact with food items. Thickness: 2mm.

Blue	
Red	
Orange	
Yellow	
Grey	


PERFORATED CANVAS

Polyester fabric 1100 dtex coated with PVC. Available two options:



ISOLATION CANVAS

Polyester fabric 1100 dtex coated with PVC. Available two options:




For further information, please consult our detailed product catalogues:



General Catalogue
Industrial doors and loading bay equipment



Loading bay equipment:
loading docks, safety systems and lifting tables




Sectional Doors



Speed Doors

Industrial doors and loading bay equipment

We are present in more than 50 countries
EUROPE, AFRICA, LATIN AMERICA, MIDDLE EAST



@angelmirporbisa



angelmirporbisa



angelmirporbisa



angelmirporbisa

Distributor:



73 Gladstone Street, Kirkby-in-Ashfield
Nottinghamshire NG17 7HS

☎ 07976 591906

✉ steve@pearsonindustrialdoors.co.uk

🌐 pearsonindustrialdoors.co.uk